

| i-Lift No. | | 1210901 | 1210902 | 1210903 | 1210904 | 1210905 | 1210906 |
|------------------------------|-----------|------------|--------------|-------------|--------------|--------------|---------------|
| Model | | ID250 | ID500 | ID1000 | ID2000 | ID3200 | ID6400 |
| Max Capacity | lbs. (kg) | 550 (250) | 1100 (500) | 2200 (1000) | 4400 (2000) | 7000 (3200) | 14000 (6400) |
| Precision | lbs. (kg) | 4 (2) | 8 (4) | 16 (8) | 30 (15) | 50 (25) | 100 (50) |
| Indexing Accuracy | lbs. (kg) | 1 (0.5) | 2 (0.9) | 2 (0.9) | 10 (4.5) | 10 (4.5) | 20 (9) |
| Test Capacity | lbs. (kg) | 1100 (500) | 2200 (1000) | 4400 (2000) | 8800 (4000) | 14000 (6400) | 28000 (12800) |
| Net Weight | lbs. (kg) | | 1.1 (0.5) | | 1.3 (0.6) | 1.5 (0.7) | 2.3 (1) |
| Figure dimension in. (mm) | A | | 8.66 (220) | | 9.17 (233) | 9.57 (234) | 10.8 (274) |
| | B | | 3.54 (89.9) | | 3.54 (89.9) | 3.81 (96.8) | 4.52 (114.8) |
| | C | | 1.65 (41.9) | | | 1.89 (48.0) | |
| | ØD | | 0.55 (14.0) | | 0.86 (21.8) | 0.86 (21.8) | 1.1 (27.9) |
| | E | | 7.71 (195.8) | | 8.15 (207.0) | 8.15 (207.0) | 8.54 (216.9) |
| | F | | 0.47 (11.9) | | 0.51 (12.7) | 0.71 (18.0) | 1.14 (29) |
| | G | | 1.38 (31.5) | | 1.77 (45.0) | 1.77 (45.0) | 2.13 (54.1) |
| | H | | 1.43 (36.3) | | 1.83 (46.5) | 2.2 (55.9) | 2.75 (69.9) |
| | I | | 0.62 (15.7) | | | 1.0 (25.4) | |
| | J | | 1.06 (26.9) | | | 1.3 (33.0) | |
| | | | 0.4 (10.2) | | | 0.4 (10.2) | |

i-LIFT load indicator feature include, high accuracy, lightweight design, easy to read display, easy to use, excellent quality, sturdy design, retains the maximum value to memory.