



LWR75-5

i-lift No.	2212401	2212402	2212403	2212404	2212405	2212406	2212407	2212408	2212409	2212410	2212411	2212412					
Model	LWR75-5	LWR100-5	LWR150-5	LWR200-5	LWR300-5	LWR600-5	LWR75-10	LWR100-10	LWR150-10	LWR200-10	LWR300-10	LWR600-10					
Rated Capacity kg(lb.)	750(1650)	1000(2200)	1500(3300)	2000(4400)	3000(6600)	6000(13200)	750(1650)	1000(2200)	1500(3300)	2000(4400)	3000(6600)	6000(13200)					
Standard Lifting Height mm(in.)/foot	1500(60)/5																
Effort to Rated Capacity (N)	150	160	230	250	350	370	150	160	230	250	350	370					
Dia. of Load Chain mm(in.)	Φ6x18(0.2x0.7)		Φ8x24(0.4x1)		Φ10x30(0.4x1.2)		Φ6x18(0.2x0.7)		Φ8x24(0.4x1)		Φ10x30(0.4x1.2)						
Net Weight kg(lb.)	7.6(16.7)	7.8(17.2)	11.5(25.3)	13.1(28.8)	21.3(46.8)	32(70.4)	7.5(16.5)	7.7(16.9)	11.5(25.3)	12.8(28.2)	21(46.2)	31.5(69.3)					
Dimensions mm(in.)	A	320(12.6)	328(12.9)	380(15)	385(15.2)	475(18.7)	495(19.5)	320(12.6)	328(12.9)	380(15)	385(15.2)	475(18.7)	495(19.5)				
	B	25(1)	30(1.2)	32(1.3)	33(1.3)	40(1.6)	50(2)	25(1)		33(1.3)	40(1.6)	50(2)					
	C	25(1)	30(1.2)	32(1.3)	38(1.5)	40(1.6)	45(1.8)	25(1)	35(1.4)	38(1.5)	52(2.1)						
	D	18(0.7)	20(0.8)	25(1)	29(1.1)	32(1.3)	40(1.6)	18(0.7)	20(0.8)	22(0.9)	26(1.1)	33(1.3)					
	E	330(13)		460(18.1)				330(13)		460(18.1)							
	F	135(5.3)		160(6.3)		211(8.3)		254(10)		135(5.3)		162(6.3)		211(8.3)		254(10)	
	G	40(1.6)	45(1.8)	52(2)	58(2.3)	65(2.6)	80(3.1)	37(1.4)	38(1.5)	45(1.8)	47(1.9)	60(2.3)	80(3.1)				
	H	58(2.3)	62(2.4)	65(2.5)	83(3.3)	75(3)	80(3.1)	58(2.3)	62(2.4)	65(2.5)	83(3.2)	75(2.9)	80(3.1)				
	J	148(5.8)		175(6.9)		195(7.7)		148(5.8)		175(6.9)		195(7.7)					
K	60(2.4)		70(2.8)		85(3.3)		60(2.4)		70(2.8)		85(3.3)						
L	88(3.5)		102(4)		109(4.3)		88(3.5)		102(4)		109(4.3)						