



i-Lift No.		2210301	2210302	2210303	2210304	2210305	2210306	2210307	2210308	2210309
Model		TW25	TW50	TW75	TW100	TW150	TW200	TW300	TW600	TW900
Rated Capacity	kg(lb.)	250(500)	500(1100)	750(1650)	1000(2200)	1500(3300)	2000(4400)	3000(6600)	6000(13200)	9000(19800)
Standard Lifting Height	mm(in.)	1000(40)	1500(60)	1500(60)	1500(60)	1500(60)	1500(60)	1500(60)	1500(60)	1500(60)
Test Load	(KN)	375	750	1125	1500	2250	3000	4500	9000	13500
Effort to Rated Capacity	(N)	282	248	265	270	295	315	335	370	420
No. of Load Chain Falls		1	1	1	1	1	1	1	2	3
Diameter of Load Chain	mm(in.)	Φ4x12 (0.2x0.4)	Φ5x15 (0.2x0.6)	Φ5.6x17 (0.2x0.7)	Φ6x18 (0.2x0.7)	Φ7.1x21 (0.3x0.8)	Φ8x24 (0.3x1)	Φ10x28 (0.4x1.1)	Φ10x28 (0.4x1.1)	Φ10x28 (0.4x1.1)
Min . Distance between Hooks	H mm(in.)	245(9.6)	300(11.8)	330(13)	365(14.4)	400(15.7)	445(17.5)	520(20.5)	640(25.2)	770(30.3)
Length of Lever Handle	D mm(in.)	158(6.2)	253(10)	278(10.9)	278(10.9)	378(14.9)	378(14.9)	388(15.3)	388(15.3)	388(15.3)
Dimensions	A mm(in.)	92(3.6)	143(5.7)	148(5.8)	153(6)	173(6.8)	181(7.1)	200(8)	200(8)	200(8)
	B mm(in.)	71(2.8)	86(3.4)	87(3.4)	90(3.5)	99(3.9)	105(4)	112(4.5)	112(4.5)	112(4.5)
	C mm(in.)	70(2.8)	118(4.6)	132(5.2)	140(5.5)	145(5.7)	152(6)	199(7.9)	230(9)	338(13.3)
	Ø mm(in.)	31(1.2)	31.5(1.2)	35.5(1.4)	37.5(1.5)	42.5(1.7)	45(1.8)	50(2)	53(2.1)	67(2.6)
	E mm(in.)	20(0.8)	24(0.9)	27(1.1)	29(1.1)	33.5(1.3)	36(1.4)	40(1.6)	42.5(1.7)	53(2.1)
Net Weight	kg(lb.)	2.1(4.6)	5.3(11.7)	6.5(14.3)	6.8(15)	10.2(22.4)	14.3(31.5)	22(48.4)	34(74.8)	45(99)