



CH25-CH300A

CH300B-CH500

CH750

CH1000

i-Lift No.		2110201	2110202	2110203	2110204	2110205	2110206	2110207	2110208	2110209	2110210
Model		CH25	CH50	CH100	CH150	CH200	CH300A	CH300B	CH500	CH750	CH1000
Rated Capacity	kg(lb.)	250(500)	500(1100)	1000(2200)	1500(3300)	2000(4400)	3000(6600)	3000(6600)	5000(11000)	7500(16500)	10000(22000)
Standard Lifting Height	mm(in.)	2500(10)	2500(10)	2500(10)	2500(10)	2500(10)	3000(120)	3000(120)	3000(120)	3000(120)	3000(120)
No. of Load Chain Falls		1	1	1	1	1	1	2	2	3	4
Dia. of Load Chain	DxT (mm)(in.)	Ø4x12 (0.2x0.5)	Ø5x15 (0.2x0.6)	Ø6x18 (0.2x0.7)	Ø7x21 (0.3x0.8)	Ø8x24 (0.3x0.9)	Ø10x28 (0.4x1.1)	Ø7x21 (0.3x0.8)	Ø9x27 (0.4x1.1)	Ø9x27 (0.4x1.1)	Ø9x27 (0.4x1.1)
Effort to Rated Capacity	(N)	235	240	250	265	335	372	290	360	365	380
Dimensions	A (mm)(in.)	121(4.8)	148(5.8)	172(6.8)	196(7.7)	210(8.3)	255(10)	230(9)	280(11)	433(17)	463(18.2)
	B (mm)(in.)	114(4.5)	132(5.2)	151(5.9)	173(6.8)	175(6.9)	205(8.2)	176(6.9)	189(7.4)	189(7.4)	189(7.4)
	C (mm)(in.)	21(0.8)	23(0.9)	27(1.1)	33(1.2)	35(1.3)	39(1.5)	39(1.5)	45(1.8)	47(1.9)	54(2.1)
	D (mm)(in.)	31(1.2)	35(1.4)	40(1.6)	45(1.8)	50(2)	55(2.2)	55(2.2)	65(2.5)	67(2.6)	75(3)
	H (min)(in.)	280(11)	345(13.6)	376(14.8)	442(17.4)	470(18.5)	548(21.8)	565(22.2)	688(27.1)	690(27.2)	765(30)
Net Weight	kg(lb.)	6.2(13.6)	11(24.2)	12.5(27.5)	17.8(39.2)	19.5(42.9)	35(77)	29(63.8)	41.3(40.9)	62(136.4)	78.5(172.7)