| Model                    | DT-20/30/50/100W                                       |
|--------------------------|--|
| Laser wavelength         | 1064nm   |
| Laserpower               | 20W 30W 50W 100W                                       |
| Repetition frequency     | 0-100KHz   |
| Minimum line width       | 0.012mm  |
| Marking range            | 100mm*100mm-300mm*300mm                                |
| Marking depth            | ≤0.4mm (by materials)                                  |
| Marking speed            | ≤1000mm/s  |
| Repeatability            | ±0.001mm   |
| Power supply requirement | 110V/220V/single-phase/50Hz/3A                         |
| Total Power              | 500W (powersaving)                                     |
| Cooling method           | Built-in air cooling                                   |
| File format              | All font/font of WINDOWS operating system font library |
| Operating system         | Windows latest system win10 system                     |
| Computer                 | Yes  |
| Red laser target         | Yes  |

## Standard accessories:

Galvanometer, field lens (100x100 or 150x150), Control card and software, red light marking range indicator, foot switch, Hexagon wrench, protective glasses, Aluminum fixing bar, Hexagon socket screws, u disk

## Optional accessories:

Red light focus indicator, Rotary table, two-dimensional table, Electric lift function, Siemens electrical components, field lens (200x200, 300x300)