

Model	KSZTA-12004	KSZTA-12006	KSJT01
Inlet Air Flow	7000/8500/13000±500 m3/h	8500/15000/19000±500 m3/h	7200-9000 m3/h
Motor Power	5.5/7.5/11 kW	7.5/11/15 kW	4.5/6.6 kW
Power Supply	3x 380V/50Hz	3x 380V/50Hz	3x380V/50Hz
Filter Material	Polyester + PTFE	Polyester + PTFE	Polyester + PTFE
Filtration Area	144 m <sup>2</sup>	216 m <sup>2</sup>	108 m <sup>2</sup>
Filtration Efficiency	≥99.9%	≥99.9%	≥99.9%
Filtration Precision	≥0.3μm	≥0.3μm	≥0.3μm
Filter Cartridge	4 PCS	6 PCS	3 PCS
Cleaning Method	Automatic Cleaning	Automatic Cleaning	Automatic Cleaning
Compressed Air	0.5~0.6 MPa	0.5~0.6 MPa	0.5~0.6 MPa
Noise Level	≤75±5 dB	≤75±5 dB	≤75±5 dB
Dimension(WxDxH)	1900×1280×3600 mm	1900×1690×3600 mm	φ1200×3650 mm
Weight	1410±50 kg	1410±50 kg	650±20 kg