

Model	KSDC-12004	KSDC-12006	KSDC-12009	KSDC-12012	KSDC-12016
Inlet Air Flow	5500/6500/9000/12500±500m 3/h	9000/14000/17000±500m 3/h	21000/24000/28000±500m 3/h	30000/36000±500m3/ h	30000/36000/42000~45000±500 m3/h
Motor Power	4/5.5/7.5/11 kW	7.5/11/15 kW	18.5/22/30 kW	30/37 kW	30/37/45 kW
Power Supply	3x 380V/50Hz	3x 380V/50Hz	3x 380V/50Hz	3x 380V/50Hz	3x380V/50Hz
Filter Material	Polyester + PTFE	Polyester + PTFE	Polyester + PTFE	Polyester + PTFE	Polyester + PTFE
Filtration Area	144 m ²	216 m ²	324 m ²	432 m ²	576 m ²
Filtration Efficiency	≥99.9%	≥99.9%	≥99.9%	≥99.9%	≥99.9%
Filtration Precision	≥0.3μm	≥0.3μm	≥0.3μm	≥0.3μm	≥0.3μm
Filter Cartridge	4 PCS	6 PCS	9 PCS	12 PCS	16 PCS
Cleaning Method	Automatic Cleaning	Automatic Cleaning	Automatic Cleaning	Automatic Cleaning	Automatic Cleaning
Compressed Air	0.5~0.6 MPa	0.5~0.6 MPa	0.5~0.6 MPa	0.5~0.6 MPa	0.5~0.6 MPa
Noise Level	≤78±5 dB	≤78±5 dB	≤78±5 dB	≤78±5 dB	≤78±5 dB
Dimension(WxDxH)	1160×960×3600 mm	1160×1320×3600 mm	1570×1320×3800 mm	1570×1680×3800 mm	1990×1680×3800 mm
Weight	860±20 kg	960/960/990±20 kg	1780±20 kg	1780±20 kg	2150±20 kg