

Model	KSDC-6102	KSDC-6103	KSDC-6104
Fan Air Flow	3000±100 m3/h	3600±100 m3/h	6000±100 m3/h
Inlet Air Flow	2400 m3/h	2600 m3/h	4000 m3/h
Motor Power	1.5kW	2.2kW	3.0kW
Power Supply	3x 380V/50Hz	3x 380V/50Hz	3x380V/50Hz
Filter Material	Polyester + PTFE	Polyester + PTFE	Polyester + PTFE
Filtering Area	20 m <sup>2</sup>	30 m <sup>2</sup>	40 m <sup>2</sup>
Filtering Efficiency	≥99.9%	≥99.9%	≥99.9%
Filtration Precision	≥0.3μm	≥0.3μm	≥0.3μm
Filter Cartridge	2 PCS	3 PCS	4 PCS
Cleaning Method	Automatic cleaning	Automatic cleaning	Automatic cleaning
Compressed Air	0.5~0.6 MPa	0.5~0.6 MPa	0.5~0.6 MPa
Noise Level	≤75±5 dB	≤75±5 dB	≤75±5 dB
Dimension(WxDxH)	720×700×1745mm	900×850×1775mm	1100×800×2000mm
Weight	225±10 kg	275±10 kg	435±10 kg