

Model	KSDC-8604A/A1	KSDC-8604B/B1	KSDC-8606B/B1	KSDC-8609B/B1	KSDC-8609B2
Fan Air Flow	6500/8200±300 m3/h	6000/8000±300 m3/h	8000/12000±500 m3/h	8000/12000±500 m3/h	15500±500 m3/h
Inlet Air Flow	4500/6800m3/h	5000/6500m3/h	6500/9500m3/h	6500/9500m3/h	13500m3/h
Motor Power	5.5/7.5kW	5.5/7.5KW	7.5/11KW	7.5/11KW	15kW
Power Supply	3x380V/50Hz	3x380V/50Hz	3x380V/50Hz	3x380V/50Hz	3x380V/50Hz
Filter Material	Polyester + PTFE	Polyester + PTFE	Polyester + PTFE	Polyester + PTFE	Polyester + PTFE
Filtration Area	60m ²	60m ²	90m ²	135m ²	135m ²
Filtration Efficiency	≥99.9%	≥99.9%	≥99.9%	≥99.9%	≥99.9%
Filtration Precision	≥0.3um	≥0.3um	≥0.3um	≥0.3um	≥0.3um
Filter Cartridge	4 Pcs	4 Pcs	6 Pcs	9 Pcs	9 Pcs
Cleaning Method	Automatic cleaning	Automatic cleaning	Automatic cleaning	Automatic cleaning	Automatic cleaning
Compressed Air	0.5~0.6Mpa	0.5~0.6Mpa	0.5~0.6Mpa	0.5~0.6Mpa	0.5~0.6Mpa
Noise Level	≤72±5 dB	≤72±5 dB	≤75±5 dB	≤75±5 dB	≤75±5 dB
Dimension (WxDxH)	1100×1100×2750mm	1170×1663×2150mm	1620×1750×2150mm	1800×2000×2500mm	1900×2150×2400mm
Weight	750±20kg	770±20kg	1050/1120±20kg	1420 /1550±20kg	1875±20kg