



Capacity	Load Center	Model No.	Mounting Class	Mounting Class	Fork Max. Spacing	Carriage Width	Overall Width	Stabilized Arm Width	Stabilized Arm Open Range	Vertical Center of Gravity	Horizontal Center of Gravity	Weight	Effective Thickness
承载能力	载荷中心	型号	安装等级	安装等级	货叉可调最大外间距	横梁宽度	总宽	稳压臂宽度	稳压臂张臂范围	垂直重心	水平重心	自重	失载距
kg	mm		A	B	C	D	E	F	L	VCG	HCG	kg	ET
2500	500	BRH25A-1040A	ISO 2A	ISO 2A	956	1040	1070	600	1050	230	135	290	244
3000	500	BRH30A-1100B	ISO 3A	ISO 3A	1025	1100	1100	600	1360	291	141	427	299

技术参数 TECHNICAL DETAILS

压力值 Pressure (Bar)		流量值 Hydraulic Flow (L/min)		
最小 Min.	最大 Max.	最小 Min.	推荐 Rec.	最大 Max.
35	160	19	38	38

注: ① 实际的叉车/属具综合承载能力请从叉车厂方获得。

Obtain the actual capacity of the forklift and attachments from the forklift manufacturer.

② 要求叉车提供1组附加油路。

Require one additional hydraulic circles.