



Capacity 承载能力	Load Center 载荷中心	Model No. 型号	Mounting Class 安装等级	Mounting Class 安装等级	Fork Max. Spacing 货叉可调最大外间距	Carriage Width 横梁宽度	Overall Width 总宽	Vertical Center of Gravity 垂直重心	Horizontal Center of Gravity 水平重心	Weight 自重	Effective Thickness 失载距
kg	mm		A	B	C	D	E	VCG	HCG	kg	ET
					mm	mm	mm	mm	mm		mm
1500	500	BRB15A-940A	ISO 2A	ISO 2A	834	940	1070	239	73	186	160
2500	500	BRB25A-1040A	ISO 2A	ISO 2A	956	1040	1070	237	76	197	165
3000	500	BRB30A-1100B	ISO 3A	ISO 3A	1025	1100	1100	315	86	326	181

技术参数 TECHNICAL DETAILS

压力值 Pressure (Bar)		流量值 Hydraulic Flow (L/min)		
最小 Min.	最大 Max.	最小 Min.	推荐 Rec.	最大 Max.
35	160	19	38	38

- 注：① 实际的叉车/属具综合承载能力请从叉车厂方获得。
Obtain the actual capacity of the forklift and attachments from the forklift manufacturer.
- ② 要求叉车提供1组附加油路。
Require one additional hydraulic circles.