



Capacity 承载能力	Load Center 载荷中心	Model No. 型号	Mounting Class 安装等级	Min. Truck Carriage Width 叉车货叉架宽度最小值	Carriage Width 横梁宽度 W	Sideshifting Range 侧移量 S	Vertical Center of Gravity 垂直重心 VCG	Horizontal Center of Gravity 水平重心 HCG	Weight 重量 kg	Effective Thickness 叉叉厚 ET mm
6800	600	SSS70D-1190C	ISO 4A	1040	1190	150	440	43	207	84
6800	600	SSS70D-1330C	ISO 4A	1222	1330	150	440	43	235	84
6800	600	SSS70D-1532C	ISO 4A	1222	1532	150	440	43	275	84
6800	600	SSS70D-1670C	ISO 4A	1372	1670	150	440	43	302	84
6800	600	SSS70D-1700C	ISO 4A	1526	1700	150	440	43	301	84
6800	600	SSS70D-1840C	ISO 4A	1526	1840	150	440	43	317	84
6800	600	SSS70D-2400C	ISO 4A	2082	2400	150	440	43	380	84

技术参数 TECHNICAL DETAILS

压力值 Pressure (Bar)		流量值 Hydraulic Flow (L/min)		
最小 Min.	最大 Max.	最小 Min.	推荐 Rec.	最大 Max.
155	210	4	23	45

- 注：① 实际的叉车/属具综合承载能力请从叉车厂方获得。
Obtain the actual capacity of the forklift and attachments from the forklift manufacturer.
- ② 要求叉车提供1组附加油路。
Require one additional hydraulic circles.