



Capacity 承载能力	Load Center 载荷中心	Model No. 型号	Mounting Class 安装等级	Min. Truck Carriage Width 叉车货叉架宽度最小值	Carriage Width 横梁宽度 W	Sideshifting Range 侧移量 S	Vertical Center of Gravity 垂直重心 VCG	Horizontal Center of Gravity 水平重心 HCG	Weight 自重	Effective Thickness 有效厚度 ET
kg	mm			mm	mm	mm	mm	mm	kg	mm
4500	600	SSS45E-1260B	ISO 3A	1140	1260	±150	300	35.6	157	75
4500	600	SSS45E-1600B	ISO 3A	1140	1600	±150	302	42	179	75
4500	600	SSS45E-1800B	ISO 3A	1140	1800	±150	296	39	207	75
5000	600	SSS50E-1200B	ISO 3A	1140	1200	±150	311	36	150	75
5000	600	SSS50E-1350B	ISO 3A	1140	1350	±150	308	37	159	75

技术参数 TECHNICAL DETAILS

压力值 Pressure (Bar)		流量值 Hydraulic Flow (L/min)		
最小 Min.	最大 Max.	最小 Min.	推荐 Rec.	最大 Max.
155	240	4	16	20

- 注：① 实际的叉车/属具综合承载能力请从叉车厂方获得。
Obtain the actual capacity of the forklift and attachments from the forklift manufacturer.
- ② 要求叉车提供1组附加油路。
Require one additional hydraulic circles.