

G Series Fork Positioner

Capacity 承载能力	Load Center 载荷中心	Model No. 型号	Mounting Class 安装等级	Opening Range 调距范围	Min. Truck Carriage Width 叉车货叉架宽度最小值	Carriage Width 横梁宽度	Fork Pocket Width 适配货叉宽度	Vertical Center of Gravity 垂直重心	Horizontal Center of Gravity 水平重心	Weight 自重	Effective Thickness 失效距
kg	mm			O mm	mm	W mm	S mm	VCG mm	HCG mm	kg	ET mm
2500	500	FPS25G-1020A	ISO 2A	285- 935	895	1020	120	-	30	69	62
3000	500	FPS30G-1100B	ISO 3A	285-1015	935	1100	125	-	30	86	64

注：①实际的叉车/属具综合承载能力请从叉车厂方获得。
Obtain the actual capacity of the forklift and attachments from the forklift manufacturer.
②要求叉车提供2组附加油路。
Require two additional hydraulic circles.

H Series Fork Positioner

Capacity 承载能力	Load Center 载荷中心	Model No. 型号	Mounting Class 安装等级	Opening Range 调距范围	Min. Truck Carriage Width 叉车货叉架宽度最小值	Carriage Width 横梁宽度	Fork Pocket Width 适配货叉宽度	Vertical Center of Gravity 垂直重心	Horizontal Center of Gravity 水平重心	Weight 自重	Effective Thickness 失效距
kg	mm			O mm	mm	W mm	S mm	VCG mm	HCG mm	kg	ET mm
4600	600	FPS46H-1000B	ISO 3A	300- 900	895	1000	150	-	35	140	75
4600	600	FPS46H-1190B	ISO 3A	300-1090	935	1190	150	-	35	160	75
5500	600	FPS55H-1190C	ISO 4A	350-1090	935	1190	150	-	40	190	75
5500	600	FPS55H-1500C	ISO 4A	350-1400	935	1500	150	-	40	230	75
7000	600	FPS70H-1190C	ISO 4A	350-1090	935	1190	150	-	45	220	80
7000	600	FPS70H-1500C	ISO 4A	350-1400	935	1500	150	-	45	260	80

注：①实际的叉车/属具综合承载能力请从叉车厂方获得。
Obtain the actual capacity of the forklift and attachments from the forklift manufacturer.
②要求叉车提供2组附加油路。
Require two additional hydraulic circles.

K Series Fork Positioner

Capacity 承载能力	Load Center 载荷中心	Model No. 型号	Mounting Class 安装等级	Opening Range 调距范围	Min. Truck Carriage Width 叉车货叉架宽度最小值	Carriage Width 横梁宽度	Fork Pocket Width 适配货叉宽度	Vertical Center of Gravity 垂直重心	Horizontal Center of Gravity 水平重心	Weight 自重	Effective Thickness 失效距
kg	mm			O mm	mm	W mm	S mm	VCG mm	HCG mm	kg	ET mm
2500	500	FPS25K-1020A	ISO 2A	260-895	895	1020	100	225	30	66	62
3000	600	FPS30K-1100B	ISO 3A	305-975	935	1100	122	290	31	85	64

注：①实际的叉车/属具综合承载能力请从叉车厂方获得。
Obtain the actual capacity of the forklift and attachments from the forklift manufacturer.
②要求叉车提供2组附加油路。
Require one additional hydraulic circles.

技术参数 TECHNICAL DETAILS							
型号 Model	压力值 Pressure (Bar)	流量值 Hydraulic Flow (L/min)					
		调距动作 Position			侧移动作 Sideshifting		
		最大 Max.	最小 Min.	推荐 Rec.	最大 Max.	最小 Min.	推荐 Rec.
25G/25H/25K	240	4	8	11	4	8	11
30G/30H/30K	240	4	8	11	4	8	11