



Capacity 承载能力	Load Center 载荷中心	Model No. 型号	Mounting Class 安装等级	Faceplate Size 推板尺寸 A * B	Platen Size 叉板尺寸 W * L	Platen Outer Spacing 叉板外间距 C	Push Stroke 推出行程 S	Min. Carriage Width 最小货叉架宽度	Horizontal Center of Gravity 水平重心 HCG	Weight 自重 kg	Effective Thickness 失效距 ET mm
------------------	---------------------	-----------------	------------------------	---------------------------------	------------------------------	------------------------------------	--------------------------	--------------------------------	---	--------------------	--

滑板可留型 Sheet-Save Types

1600	600	QPA16E-001A	ISO 2A	1015*1000	455*1220	1020/1170	1270	820	241	494	220
1600	600	QPA16E-001B	ISO 3A	1015*1000	455*1220	1020/1170	1270	820	241	494	220
1600	600	QPA16E-002A	ISO 2A	1015*1000	380*1220	870/1020	1270	820	227	481	220
1600	600	QPA16E-002B	ISO 3A	1015*1000	380*1220	870/1020	1270	820	227	481	220
2000	600	QPA20E-001A	ISO 2A	1015*1000	455*1220	1020/1170	1270	820	245	499	220
2000	600	QPA20E-001B	ISO 3A	1015*1000	455*1220	1020/1170	1270	820	245	499	220
2000	600	QPA20E-002A	ISO 2A	1015*1000	380*1220	870/1020	1270	820	231	486	220
2000	600	QPA20E-002B	ISO 3A	1015*1000	380*1220	870/1020	1270	820	231	486	220

滑板不可留型 Without Sheet-Save Types

1600	600	QPB16E-001A	ISO 2A	1015*1000	455*1220	1020/1170	1270	820	237	381	185
1600	600	QPB16E-001B	ISO 3A	1015*1000	455*1220	1020/1170	1270	820	237	381	185
1600	600	QPB16E-002A	ISO 2A	1015*1000	380*1220	870/1020	1270	820	222	370	185
1600	600	QPB16E-002B	ISO 3A	1015*1000	380*1220	870/1020	1270	820	222	370	185
2000	600	QPB20E-001A	ISO 2A	1015*1000	455*1220	1020/1170	1270	820	241	386	185
2000	600	QPB20E-001B	ISO 3A	1015*1000	455*1220	1020/1170	1270	820	241	386	185
2000	600	QPB20E-002A	ISO 2A	1015*1000	380*1220	870/1020	1270	820	226	375	185
2000	600	QPB20E-002B	ISO 3A	1015*1000	380*1220	870/1020	1270	820	226	375	185

技术参数 TECHNICAL DETAILS

型号 Model	压力值 Pressure (Bar)		流量值 Hydraulic Flow (L/min)		
	最小 Min.	最大 Max.	最小 Min.	推荐 Rec.	最大 Max.
16E	-	160	15	26	38
20E	-	160	15	26	38

注：① 实际的叉车/属具综合承载能力请从叉车厂方获得。

Obtain the actual capacity of the forklift and attachments from the forklift manufacturer.

② 要求叉车提供1组附加油路。

Require one additional hydraulic circles.

③ 重要提示：快装型推拉器必须同时挂装标准货叉（货叉同时承受推拉器和货物的重量），货叉厚度为35~45mm之间，长度为1015~1170mm，推荐货叉长度为1060mm，两货叉内间距为550~650mm。货叉厚度超过40mm时，需要增加垫片组件。

IMPORTANT: QFM Push Pull must be mounted on standard forks to support the load and push/pull. Fork thickness is between 35 to 45mm, length is 1015 to 1170mm. Recommended for length is 1060mm. Forks must be spaced 550 to 650mm. Forks over 40mm thick required spacer kit.

④ QPA型带电磁阀（未注明情况下，工作电压为12V），请注意所选配叉车系统电压值。

QPA model is equipped solenoid valve (if no special notice the voltage is 12V), solenoid valve voltage should match truck voltage.