



Capacity 承载能力	Load Center 载荷中心	Model No. 型号	Mounting Class 安装等级	Opening Range 货叉张距	Fork Set Spacing 货叉净张距	Fork Size 货叉尺寸	Fork Height 货叉高度	Frame Width 框架宽度	Vertical Center of Gravity 垂直重心	Horizontal Center of Gravity 水平重心	Weight 重量	Effective Thickness 失效距
kg	mm			O	B	L*W*T	H	A	VCG	HCG	kg	ET
2200	600	FDS22E-010A	ISO 2A	640-2040	640	1150*80*40	1150	1100	211	239	404	182
2200	600	FDS22E-010B	ISO 3A	640-2040	640	1150*80*40	1150	1100	211	239	404	182
2500	600	FDS25E-010B	ISO 3A	640-2040	640	1150*80*50	1400	1100	234	258	460	192

**技术参数 TECHNICAL DETAILS**

型号 Model	压力值 Pressure (Bar)	流量值 Hydraulic Flow (L/min)					
		侧移动作 Sideshifting			张夹动作 Clamp		
		最大 Max.	最小 Min.	推荐 Rec.	最大 Max.	最小 Min.	推荐 Rec.
22E	160	4	8	11	15	26	26
25E	160	4	8	11	15	26	26

注：① 实际的叉车/属具综合承载能力请从叉车厂方获得。  
 Obtain the actual capacity of the forklift and attachments from the forklift manufacturer.  
 ② 要求叉车提供2组附加油路。  
 Require two additional hydraulic circles.  
 ③ 侧移行程±100mm。  
 Sideshifting range is ±100mm.  
 ④ 外货叉比内货叉略高5mm。  
 The outer fork tines are 5mm higher than the inner fork tines.