



技术参数示意图 Technical parameter schematic diagram

项目Item 型号Model	最大压力 Maximum pressure(kN)	液压力 Hydraulic pressure(MPa)	压头行程 Ram stroke (mm)	压头速度 Ram speed 快/工/回 mm/s	配泵型号 Recommended pump station	电机功率 Motor power (kw)	工作台板尺寸 Size of worktable (mm)
CDY10/25	98	25.5	250	15.1/31	3.5-25动力单元	1.5	320x280
CDY20/25	196	25	250	7.4/12.3	3.5-25动力单元	1.5	360x320
CDY30/25	294	24	250	20/4.5/34	BYBZ15	2.2	400x340
CDY40/30	392	25.5	300	16.2/3.6/33	BYBZ15	2.2	480x400
CDY50/30	490	24.5	300	12.4/3/28.4	BYBZ15	2.2	500x450
CDY63/30	618	30	300	12/3/16	BYBZ15	2.2	500x400
CDY80/30	784	30	300	23/6/31	BYBZ36	5.5	650x520
CDY100/35	980	30	350	19/5/26.4	BYBZ36	5.5	780x640
CDY150/35	1470	30	350	12.2/3.1/17	BYBZ36	5.5	880x720
CDY200/35	1960	30	350	31/7/47	BYBZ116	15	1000x800
CDY300/35	2940	30	350	19/4/28	BYBZ116	15	1200x1000

项目Item 型号Model	A	B	C	D	E	I	质量 Mass (kg)
CDY10/25	650	320	950	150	280	260	590
CDY20/25	720	360	1100	180	300	320	660
CDY30/25	900	400	1250	210	300	400	1200
CDY40/30	1050	580	1700	240	350	760	1690
CDY50/30	1100	680	1750	250	400	760	1960
CDY63/30	1100	700	1750	250	400	760	2900
CDY80/30	1380	800	1950	320	470	760	3300
CDY100/35	1785	1080	2380	400	586	780	3800
CDY150/35	1950	1150	2530	450	600	790	4500
CDY200/35	2200	1250	2780	450	620	800	5300
CDY300/35	2900	1350	3400	500	900	1000	9780