



Fire resistant according to new IEC 60331-1/2 (2009) specifications, control, instrumentation, tele-and data communication cables. The tinned copper braided screen reduces Electro Magnetic Interferences (EMI) and grants extra mechanical protection. The XLHFFR isolation and variable twist lengths of the pairs provide perfect electrical properties and low capacitance for minimal signal loss. The special ripcord provides easy stripping of the outer sheath.

Characteristics	Properties	Unit
Product group	Communication marine cables	
Series	Shipboard cable	
Type	MarineCom YOZc X-FR 250 V	
Standardization	IEC 60092-350/-351/-376	
Flame retardant	IEC 60332-1 / IEC 60332-3-22 Cat. A	
Conductor category	Class 2 = stranded	
Stranding element	Pair	
Core insulation	Mica + XLHFFR	
Core identification	Numbers	
Construction outer shield	Tinned copper braiding	
Screen over stranding	Braiding	
Material outer sheath	Flame Retardant Halogen Free Polyolefin Compound	
Colour outer sheath	Orange	
Maximum conductor temperature	90	°C
Operating temperature, flexible	-20 / 70	°C
Operating temperature, fixed	-40 / 70	°C
Specification	See appendix	

Partnumber	Construction	Conductor category	Net weight (kg/km)	radius after installation (mm)	Outer diameter approx. (mm)	Tensile load (N)
26470	1 x 2 x 0,5 mm ²	Class 2 = stranded	82	32	7,9	15
26485	1 x 3 x 0,5 mm ²	Class 2 = stranded	94	33	8,2	23
26471	1 x 4 x 0,5 mm ²	Class 2 = stranded	119	37	9,3	30
26520	2 x 2 x 0,5 mm ²	Class 2 = stranded	144	69	11,5	30
26486	2 x 3 x 0,5 mm ²	Class 2 = stranded	176	75	12,5	45
26472	4 x 2 x 0,5 mm ²	Class 2 = stranded	240	83	13,8	60
26487	4 x 3 x 0,5 mm ²	Class 2 = stranded	302	91	15,2	90
26473	6 x 2 x 0,5 mm ²	Class 2 = stranded	339	98	16,4	90
26474	7 x 2 x 0,5 mm ²	Class 2 = stranded	339	98	16,4	105
26488	7 x 3 x 0,5 mm ²	Class 2 = stranded	449	113	18,8	158
26475	8 x 2 x 0,5 mm ²	Class 2 = stranded	382	106	17,6	120
26476	10 x 2 x 0,5 mm ²	Class 2 = stranded	456	120	20	150
26489	10 x 3 x 0,5 mm ²	Class 2 = stranded	613	137	22,8	225
26477	12 x 2 x 0,5 mm ²	Class 2 = stranded	515	125	20,8	180



Partnumber	Construction	Conductor category	Net weight (kg/km)	Bending radius after installation (mm)	Outer diameter approx. (mm)	Tensile load (N)
26478	14 x 2 x 0,5 mm ²	Class 2 = stranded	576	134	22,3	210
26490	14 x 3 x 0,5 mm ²	Class 2 = stranded	778	152	25,3	315
26479	19 x 2 x 0,5 mm ²	Class 2 = stranded	740	153	25,5	285
26491	19 x 3 x 0,5 mm ²	Class 2 = stranded	986	173	28,8	428
26480	24 x 2 x 0,5 mm ²	Class 2 = stranded	891	169	28,2	360
26492	24 x 3 x 0,5 mm ²	Class 2 = stranded	1196	192	32	540
26481	27 x 2 x 0,5 mm ²	Class 2 = stranded	965	178	29,6	405
26482	30 x 2 x 0,5 mm ²	Class 2 = stranded	1070	187	31,2	450
26483	37 x 2 x 0,5 mm ²	Class 2 = stranded	1268	205	34,2	555
26500	1 x 2 x 0,75 mm ²	Class 2 = stranded	91	33	8,2	23
26515	1 x 3 x 0,75 mm ²	Class 2 = stranded	107	33	8,2	34
26501	1 x 4 x 0,75 mm ²	Class 2 = stranded	137	38	9,5	45
26502	2 x 2 x 0,75 mm ²	Class 2 = stranded	165	73	12,2	45
26516	2 x 3 x 0,75 mm ²	Class 2 = stranded	231	81	13,5	68
26503	4 x 2 x 0,75 mm ²	Class 2 = stranded	245	86	14,3	90
26517	4 x 3 x 0,75 mm ²	Class 2 = stranded	349	96	16	135
26504	6 x 2 x 0,75 mm ²	Class 2 = stranded	356	103	17,1	135
26505	7 x 2 x 0,75 mm ²	Class 2 = stranded	366	103	17,1	158
26518	7 x 3 x 0,75 mm ²	Class 2 = stranded	539	121	20,1	236
26506	8 x 2 x 0,75 mm ²	Class 2 = stranded	404	109	18,1	180
26507	10 x 2 x 0,75 mm ²	Class 2 = stranded	549	126	21	225
26519	10 x 3 x 0,75 mm ²	Class 2 = stranded	729	145	24,2	338
26508	12 x 2 x 0,75 mm ²	Class 2 = stranded	631	133	22,2	270
26509	14 x 2 x 0,75 mm ²	Class 2 = stranded	710	142	23,6	315
26521	14 x 3 x 0,75 mm ²	Class 2 = stranded	936	161	26,8	473
26510	19 x 2 x 0,75 mm ²	Class 2 = stranded	898	161	26,9	428
26522	19 x 3 x 0,75 mm ²	Class 2 = stranded	1228	185	30,8	641
26511	24 x 2 x 0,75 mm ²	Class 2 = stranded	1087	179	29,8	540
26523	24 x 3 x 0,75 mm ²	Class 2 = stranded	1494	205	34,2	810
26512	27 x 2 x 0,75 mm ²	Class 2 = stranded	1214	189	31,5	608
26513	30 x 2 x 0,75 mm ²	Class 2 = stranded	1332	199	33,2	675
26514	37 x 2 x 0,75 mm ²	Class 2 = stranded	1574	217	36,2	833
26526	1 x 2 x 1 mm ²	Class 2 = stranded	106	36	8,9	30
26541	1 x 3 x 1 mm ²	Class 2 = stranded	124	37	9,3	45
26527	1 x 4 x 1 mm ²	Class 2 = stranded	152	41	10,2	60
26528	2 x 2 x 1 mm ²	Class 2 = stranded	215	80	13,4	60
26542	2 x 3 x 1 mm ²	Class 2 = stranded	268	88	14,6	90
26543	4 x 3 x 1 mm ²	Class 2 = stranded	406	103	17,2	180
26532	8 x 2 x 1 mm ²	Class 2 = stranded	516	120	20	240
26533	10 x 2 x 1 mm ²	Class 2 = stranded	637	136	22,7	300
26545	10 x 3 x 1 mm ²	Class 2 = stranded	852	156	26	450
26534	12 x 2 x 1 mm ²	Class 2 = stranded	711	142	23,7	360
26535	14 x 2 x 1 mm ²	Class 2 = stranded	802	151	25,2	420
26546	14 x 3 x 1 mm ²	Class 2 = stranded	1099	173	28,8	630
26536	19 x 2 x 1 mm ²	Class 2 = stranded	1036	175	29,1	570
26547	19 x 3 x 1 mm ²	Class 2 = stranded	1443	199	33,2	855
26537	24 x 2 x 1 mm ²	Class 2 = stranded	1259	193	32,2	720

Partnumber	Construction	Conductor category	Net weight (kg/km)	Bending radius after installation (mm)	Outer diameter approx. (mm)	Tensile load (N)
26548	24 x 3 x 1 mm ²	Class 2 = stranded	1840	223	37,2	1080
26538	27 x 2 x 1 mm ²	Class 2 = stranded	1398	205	34,1	810
26539	30 x 2 x 1 mm ²	Class 2 = stranded	1613	216	36	900
26540	37 x 2 x 1 mm ²	Class 2 = stranded	1917	238	39,6	1110
26550	1 x 2 x 1,5 mm ²	Class 2 = stranded	127	39	9,7	45
26551	1 x 4 x 1,5 mm ²	Class 2 = stranded	192	45	11,3	90
26552	2 x 2 x 1,5 mm ²	Class 2 = stranded	274	91	15,1	90
26566	2 x 3 x 1,5 mm ²	Class 2 = stranded	337	98	16,3	135
26553	4 x 2 x 1,5 mm ²	Class 2 = stranded	405	106	17,6	180
26567	4 x 3 x 1,5 mm ²	Class 2 = stranded	531	118	19,6	270
26554	6 x 2 x 1,5 mm ²	Class 2 = stranded	552	126	21	270
26568	7 x 3 x 1,5 mm ²	Class 2 = stranded	812	146	24,4	473
26555	8 x 2 x 1,5 mm ²	Class 2 = stranded	677	135	22,5	360
26556	10 x 2 x 1,5 mm ²	Class 2 = stranded	821	154	25,7	450
26569	10 x 3 x 1,5 mm ²	Class 2 = stranded	1135	179	29,8	675
26557	12 x 2 x 1,5 mm ²	Class 2 = stranded	922	161	26,8	540
26558	14 x 2 x 1,5 mm ²	Class 2 = stranded	1058	173	28,8	630
26570	14 x 3 x 1,5 mm ²	Class 2 = stranded	1487	199	33,2	945
26559	19 x 2 x 1,5 mm ²	Class 2 = stranded	1370	197	32,9	855
26571	19 x 3 x 1,5 mm ²	Class 2 = stranded	2027	232	38,6	1283
26560	24 x 2 x 1,5 mm ²	Class 2 = stranded	1769	223	37,1	1080
26572	24 x 3 x 1,5 mm ²	Class 2 = stranded	2479	257	42,8	1620
26561	27 x 2 x 1,5 mm ²	Class 2 = stranded	1961	235	39,2	1215
26562	30 x 2 x 1,5 mm ²	Class 2 = stranded	2142	246	41	1350
26563	37 x 2 x 1,5 mm ²	Class 2 = stranded	2580	272	45,3	1665
26575	1 x 2 x 2,5 mm ²	Class 2 = stranded	157	64	10,7	75
26565	1 x 3 x 2,5 mm ²	Class 2 = stranded	202	46	11,5	113
26590	1 x 3 x 2,5 mm ²	Class 2 = stranded	202	69	11,5	113
26576	1 x 4 x 2,5 mm ²	Class 2 = stranded	250	74	12,4	150
26577	2 x 2 x 2,5 mm ²	Class 2 = stranded	344	101	16,9	150
26591	2 x 3 x 2,5 mm ²	Class 2 = stranded	430	109	18,2	225
26592	4 x 3 x 2,5 mm ²	Class 2 = stranded	688	130	21,7	450
26593	7 x 3 x 2,5 mm ²	Class 2 = stranded	1112	165	27,5	788
26581	8 x 2 x 2,5 mm ²	Class 2 = stranded	897	152	25,4	600
26582	10 x 2 x 2,5 mm ²	Class 2 = stranded	1091	174	29	750
26594	10 x 3 x 2,5 mm ²	Class 2 = stranded	1535	201	33,5	1125
26583	12 x 2 x 2,5 mm ²	Class 2 = stranded	1267	183	30,5	900
26584	14 x 2 x 2,5 mm ²	Class 2 = stranded	1423	196	32,6	1050
26595	14 x 3 x 2,5 mm ²	Class 2 = stranded	2095	226	37,6	1575
26585	19 x 2 x 2,5 mm ²	Class 2 = stranded	1957	227	37,9	1425
26596	19 x 3 x 2,5 mm ²	Class 2 = stranded	2746	259	43,2	2138
26586	24 x 2 x 2,5 mm ²	Class 2 = stranded	2415	253	42,2	1800
26597	24 x 3 x 2,5 mm ²	Class 2 = stranded	3398	289	48,1	2700
26587	27 x 2 x 2,5 mm ²	Class 2 = stranded	2685	268	44,6	2025
26588	30 x 2 x 2,5 mm ²	Class 2 = stranded	2955	280	46,7	2250
26589	37 x 2 x 2,5 mm ²	Class 2 = stranded	3587	310	51,7	2775