



ELECTRONIC TIME RECORDER

EX3500N

Once the unit has been programmed, it is completely "Hands-Off". There is no need for Occasional Time and Date adjustments necessary with mechanical Time Recorders. The EX-3500N is equipped with a perpetual calendar, which allows the machine to automatically adjust to the end of every month, leap years, and even Daylight-Saving Time.



AMANO

ELECTRONIC TIME RECORDER

EX3500N

PRECISION HAS NEVER BEEN SO ECONOMICAL

High-quality dot matrix printer for clean, clear printing

Printing irregular work in red color

Programmable IN/OUT Printing position

6 column printing

MAIN FEATURES

- Simple, clean design fits any business environment
- Simple and Easy Operation
- Large, easy-to-read analog clock face with quartz time base.
- Surface detection function for right side of time card
- Automatic adjustment of Daylight-Saving Time, short months, leap years
- Automatic card feeding, standard
- Auto IN/OUT shift
- Two color printing
- Time Signal



White

Black

No. <u>48</u>		PAY ENDING <u>April</u> .20 <u>03</u>					
NAME <u>Jason Brown</u>							
	HOURS	RATE	AMOUNT	DEDUCTIONS	INCOME TAX	\$ 180.00	
R.T.	186.5	\$ 6.00	\$ 1,119.00		UNEMP. INS.	\$ 20.00	
O.T.	10	\$ 9.00	\$ 90.00		HOSP.		
					BONDS		
TOTAL EARNINGS			\$ 1,209.00	MISC.			
TOTAL DEDUCTIONS			\$ 200.00				
BALANCE DUE			\$ 1,009.00	TOTAL	\$ 200.00		
DATE	MORNING		AFTERNOON		OVERTIME		HRS
	IN	OUT	IN	OUT	IN	OUT	
1	8:28	12:02	12:58	17:36			8
2	8:34	12:03	12:57	17:39	17:45	19:46	9.5
3	8:27	12:01	12:54	17:33			8
4	8:29	12:04	13:02	17:38			7.5
5	8:28	12:10					3.5
6							
7	8:28	12:01	12:58	15:00			5.5
8	8:28	12:03	12:58	17:36			8
9	8:29	11:55	12:59	17:31	18:00	20:03	9.5
10	8:24	12:04	12:59	17:37			8
11	8:29	12:01	12:58	17:37			8
12	8:27	12:03					3.5
13							
14	8:22	12:08	12:58	17:32			8
15	8:29	12:01	12:55	17:38			8

THE BALANCE SHOWN ABOVE IS CORRECT AND RECEIPT IS ACKNOWLEDGED.

SIGNATURE Jason Brown

AMANO FORM A-701

Acceptable Pay Period

Pay period ending date can be set three ways.

- weekly
- bi-weekly
- monthly

BASIC SPECIFICATIONS

Printing	Dot matrix printing
Power Supply	110/120VAC or 220/240VAC ± 10% 50/60Hz
Power Consumption	110-120VAC...Stand-by 70mA, Rated 400mA 220-240VAC...Stand-by 60mA, Rated 220mA
Operating Conditions	Temperature-10 to 40 Humidity 10% to 90% RH(without condensation)
Dimensions	190(W) × 224(H) × 127(D)mm (7.1/2" × (8.6/8)" × (5")
Clock System	Quartz oscillation system, Accuracy ± 3 seconds per week(25 ± 5)(77°F ± 10°F)
Weight	2.3Kg(5.07Lbs.)
Memory holding function	Clock and programing data kept for 3 years without AC power

Specifications and descriptions contained in this catalog may be subject to change without notice.

Distributed by:

AMANO Corporation

275 MAMEDO-CHO, KOHOKU-KU, YOKOHAMA,
JAPAN 222-8558
TEL. +81-45-439-1508 FAX. +81-45-439-1151
HOME PAGE : <http://www.amano.co.jp/english/>