



Features

Magnetic lifters has strong magnetic circuit by permanent magnetic materials. On and off the magnetic circuit is controlled by turning the control handle. The working performance is stable and lasting. This series is very popular with European and American customers owing to its strong pull-off strength, high safety factor and reliable quality.

Specifications

| Model | Rated lifting strength | Cylindrical lifting strength | Max. pull-off strength | L | W | H | R | Operation temperature | Net weight |
|-----------------|------------------------|------------------------------|------------------------|-----|-----|-----|-----|-----------------------|------------|
| | Kgf | Kgf | Kgf | | | | | °C | Kg |
| PML-1 | 100 | 30 | 350 | 92 | 64 | 70 | 142 | <80 | 3 |
| PML-2 | 200 | 60 | 700 | 158 | 64 | 70 | 142 | <80 | 5 |
| PML-3 | 300 | 100 | 1050 | 165 | 88 | 96 | 176 | <80 | 10 |
| PML-5 | 500 | 150 | 1750 | 216 | 118 | 118 | 219 | <80 | 20 |
| PML-6 | 600 | 200 | 2100 | 236 | 118 | 120 | 219 | <80 | 24 |
| PML-10 | 1000 | 300 | 3500 | 264 | 168 | 168 | 285 | <80 | 50 |
| PML-15 | 1500 | 500 | 5200 | 352 | 168 | 168 | 380 | <80 | 70 |
| PML-20 | 2000 | 600 | 7000 | 378 | 226 | 216 | 462 | <80 | 125 |
| PML-30 | 3000 | 1000 | 10500 | 453 | 290 | 265 | 567 | <80 | 220 |
| PML-50 | 5000 | 1500 | 17500 | 647 | 290 | 265 | 590 | <80 | 350 |
| PML-60 | 6000 | 2000 | 19200 | 713 | 290 | 266 | 707 | <80 | 398 |
| NEW TYPE | | | | | | | | | |
| PML-10 | 1000 | 300 | 3500 | 286 | 148 | 140 | 266 | <80 | 40 |
| PML-20 | 2000 | 600 | 7000 | 397 | 188 | 185 | 400 | <80 | 95 |
| PML-30 | 3000 | 1000 | 10500 | 453 | 226 | 265 | 567 | <80 | 180 |