

One Way Lashing

The UNIFIXX One-way lashing systems offers a lashing solution by combining low cost with safe transport.

The UNIFIXX solution is much better than the traditional way of securing loads and over the last decades it has replaced traditional products such as ropes and chains. The UNIFIXX one-way lashing systems are light weight load securing solutions avoiding damage risk on heavy and expensive loads. Our high tenacity products are extremely suitable for securing loads on crates, pallets, in containers, flattracks and on wagons. The UNIFIXX One-way lashing webbing is supplied in combination with buckles and tensioners.

The UNIFIXX One-way lashing systems are approved by the Germanischer Lloyd, one of the toughest approvals. The allowable working loads vary from 500daN to 4.000 daN with a width variation from 30mm to 50mm. The lashings are produced in-house ensuring a high flexibility regarding individuals wishes. UNIFIXX can be manufactured, personalized and packed to your individual specifications.



Type	Width (mm)	MBS Lashing (daN)	Packing (plastic bags)	System Strength (daN)- Buckle
W323	32	2300	250 mtr.	4000 - B3030
W435	40	3500	200 mtr.	6000 - B4040
W450	40	5000	200 mtr.	7500 - B4040
W523	50	2300	300 mtr.	3000 - B5020
W550	50	5000	200 mtr.	9000 - B5050
W560	50	6000	150 mtr.	9500 - B5050
W575	50	7500	150 mtr.	10000 - B5050

Type	Width (mm)	
B3030	30	
B4040	40	
B5050	50	
B3030S	30	
B5020	50	
B4050W	50	
B5050W		
H5050	50	
SB10-7	32 mm	
SB12-7	40 mm	
SB12-8	40 mm	
SBF10-7	32 mm	
SBF12-7	40 mm	
SBF12-8	40 mm	



TENS26



PTENS01



UR5050