

# Marine Approved Conventional Photoelectric Smoke Detector

## SLR-EM



### Features

- ▶ Removable, High Performance chamber
- ▶ Low profile design with one piece outer cover
- ▶ Twin fire LED's allow 360° viewing
- ▶ Approved by LPCB, LRS, MSA and DNV

### Description

The CDX Range Marine Approved Photoelectric Smoke Detector with High Performance Chamber Technology is suited to a wide range of applications. It can be installed in areas where traditionally both Photoelectric and Ionisation Smoke Detectors have been used, thereby providing a simpler solution for system designers.

Specification	
Ordering Code	SLR-EM
Disposable Chamber	Yes
Operating Voltage	15 - 30Vd.c.
Quiescent Current (typ)	35µA
Maximum Current Alarm	40mA
Operating Temperature Range	-25°C to + 70°C
Storage Temperature Range	-30°C to + 60°C
Maximum Humidity	95%RH - Non Condensing (at 40°C)
Ingress Protection Rating	IP42
Colour / Case Material	Ivory White / ABS
Weight (g) / Diameter (mm) / Height (mm)	95 / 100 / 38
Compatible Bases / Base Heights (mm)	YBN-R4M / 8
	YBO-R/5M / 13
Base Fixing Centres (mm)	48 ~ 74
Approvals	LPCB, Lloyds Register, DNV, Germanischer Lloyd, MCA