



过滤减压/Filter®ulators		MINI			MIDI			MAXI	
手动放水器 Manual Drain	工作压力(Working pressure): 12bar,40µm	JOFR-1/8-MINI	JOFR-1/4-MINI	JOFR-3/8-MINI	JOFR-3/8-MIDI	JOFR-1/2-MIDI	JOFR-3/4-MIDI	JOFR-3/4-MAXI	JOFR-1-MAXI
	工作压力(Working pressure): 7bar,40µm	JOFR-1/8-7-MINI	JOFR-1/4-D-7-MINI	JOFR-3/8-7-MINI	JOFR-3/8-7-MIDI	JOFR-1/2-7-MIDI	JOFR-3/4-7-MIDI	JOFR-3/4-7-MAXI	JOFR-1-7-MAXI
	工作压力(Working pressure): 12bar,5µm	JOFR-1/8-5M-MINI	JOFR-1/4-5M-MINI	JOFR-3/8-5M-MINI	JOFR-3/8-5M-MIDI	JOFR-1/2-5M-MIDI	JOFR-3/4-5M-MIDI	JOFR-3/4-5M-MAXI	JOFR-1-5M-MAXI
Manometer	0~12bar	OMA-40-16-1/8			OMA-50-16-1/4				
	0~7bar	OMA-40-10-1/8			OMA-50-10-1/4				
工作介质 Medium	压缩空气 / Compressed air								
结构特点 Features of structure	带水分离器的烧结式过滤器; MINI/MID:膜片式减压阀; MAXI:活塞式减压阀; Sintered filter with water separator; MINI/MID:Diaphragm type-regulator; MAXI:Piston regulator;								
安装方式 Mounting type	管式安装或支架安装 / Pipe mounting or foot mounting								
安装位置 Assembly position	垂直方向(Vertical) ±5°								
连接尺寸 Connection		G1/8"	G1/4"	G3/8"	G3/8"	G1/2"	G3/4"	G3/4"	G1"
标准额定 流量 Standard nominal flow rate	JOFR-...	750	1400	1600	3100	3400	3400	9000	10000
	JOFR-...-7	900	1500	1700	3400	3900	3900	9500	16000
	JOFR-...-5M	650	1200	1350	2400	2500	2500	7300	7600
输入压力 Primary pressure	手动排水阀 Manual drain valve	1~16bar							
工作压力 Working pressure	0.5~12bar/0.5~7bar								
过滤精度 Grade of filtration	40µm/5µm								
最大凝液容量 Max. Condensate Capacity	22ml								
温度范围 Temperature range	0~60℃								
材料 Material	壳体: 压铸锌; 过滤杯和油杯: PC; 金属保护罩: 铝合金; 密封: 丁腈橡胶; 调压手轮: POM Housing: Zinc die-casting; Filter bowl; PC; Metal bowl guard: Aluminium alloy; Sealing: NBR; Adjusting knob: POM								