

CONCRETE VIBRATOR - KANDA

振动棒



Model	Vibration (vpm)	Rotating Speed (rpm)	Flexible Hose Assembly Length (m)	Vibration Head Diameter x Length (mm)
KV 25	9500 - 12500	3000	4 - 10	25 x 478
KV 28			4 - 10	28 x 442
KV 38			4 - 12	38 x 502
KV 45			4 - 12	45 x 502
KV 60			4 - 12	60 x 470
KV 75	12000 - 15000	3000	4 - 12	75 x 459

PORTABLE VIBRATOR

手提振棒



Model	Power (kW)	Current (A)	Diameter (mm)	Length (mm)	Vibration Frequency (Hz) / Amp (mm)	Weight (kg)
ZN25C-1.5	0.58	2.7	25	473	260 / 0.7	5.6
ZN35C-1.5			35	456	220 / 0.8	6.5

HANDY EXTERNAL CONCRETE VIBRATOR

手提振棒



Model	Power (W)	Current (A)	Vibration Frequency (Hz) / Amp (mm)	Face / Head Dimensions (mm)	Total Length (mm)	Weight (kg)
EKCA W/Holder	280	5	150-167 / 0.6	76 x 113	404	4.7
				120 x 150	407	5.8

