

PORTABLE DIESEL GENERATOR & SILENT GENERATOR

柴油发电机



Model	Drive Unit (Air Cooled Diesel Engine)	Max Output Kw / Kva	Frequency (Hz) / Rated Voltage (V)	Rated Current (A)	Weight (kg)	Noise Level (Full Loading) 7m db (A)
KDE2000X	Kanda 170FG 5Hp(3.7Kw)	2 (2.7Hp) / 3	50Hz 230 - 240 / 120 1 Phase	8.3	46	74
KDE3300X / KDE3300E	Kanda 178FG 6Hp(4.4Kw)	3 (4.1Hp) / 4		13	65	77
KDE6500X / KDE6500E	Kanda 186FG 10Hp(7.5Kw)	5 (6.8Hp) / 6		24	95	77 / 85
KDE6500T					171	86
KDE6500T3	Kanda 186FAG 10Hp(7.5Kw)	6 (8Hp) / 7.5		50Hz 230 - 400 3 phase	8	171

GENERATOR CUM WELDER - KANDA

柴油发电烧焊机



Model	Type	DC Output Welder	Rated Output (kW)	Weight (kg)	Welding Rod; Noise Level at db(A)@7m
KDE - 6500EW	Air Cooled 1 Cylinder, 4 Stroke 10Hp (7.5Kw) Diesel Engine	160A	1 Phase 2.8	100	2.0 - 4.0 mm; 74 - 79