



Daphne Super Hydro A Series

High Performance Hydraulic Oil

Description

Daphne Super Hydro A series of Zinc-free hydraulic fluids have been formulated with highly refined hydro-treated base oil together with anti-wear, anti-oxidant and various additives to provide superior performance in hydraulic systems.

Application

This series of hydraulic fluid is suitable for all hydraulic power units including the advanced high-pressure hydraulic power units, which operate with higher thermal load.

Characteristics

1. **Excellent Heat Resistance, Oxidation And Thermal Stability** - A highly refined hydro treated paraffin base oil and anti-oxidant assures excellent oxidation and thermal stability and reduce sticking problems caused by formation of sludge. Prevents sludge formation in the hydraulic tank and filter.
2. **Extended Oil Change** - Much longer oil change interval compared with those Zinc anti-wear type hydraulic fluids.
3. **Excellent Anti-Wear Properties** - Addition of special anti-wear agent assures excellent anti-wear properties to reduce maintenance down time.
4. **Excellent Demulsibility** - Extremely quick separation with water prevents it from emulsifying with water makes it most suitable for preventing machine parts from rust and corrosion.
5. **Low Pour Point** - Addition of pour point depressant reduces power loss and warming up time, ensuring energy conservation.

Packing

20L pail, 200L drum

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.

**Typical Specifications****Daphne Super Hydro A Series**

Available Grades	ASTM METHOD	22A	32A	46A	68A	100A	150A
Colour	D-1500	L0.5	L0.5	L0.5	L0.5	L0.5	L0.5
Density 15 °C g/cm ³	D-4052	0.8417	0.8647	0.8675	0.8706	0.8732	0.8761
Flash Point (COC) °C	D-92	218	218	230	248	268	274
Viscosity, cSt @ 40 °C	D-445	21.71	31.65	45.74	68.56	97.56	146.20
@ 100 °C		4.515	5.407	6.909	9.025	11.480	15.210
Viscosity Index	D-2270	123	105	107	106	105	105
TAN (mgKOH/g)	D-974	0.15	0.16	0.14	0.14	0.18	0.17
Pour Point °C	D-6749	-30.0	-40.0	-37.5	-30.0	-30.0	-17.5
Foaming @ 24°C	D-892	0-0	0-0	0-0	0-0	0-0	0-0

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.