

Lubricant Product Information



Daphne Super Screw Series

High Performance Super Long Life Screw Compressor Oil

Description

Daphne Super Screw Series is a range of super long life screw compressor oil formulated with highly refined mineral base oil formulated and carefully selected additives including the antioxidant for high temperature. Especially, it has super long oil service life with excellent oxidation stability, it is not affected by external contaminants such as oil mist or deteriorated residue etc. of cutting lubricant.

Application

It is formulated for screw type of compressor with super long oil service life.

Characteristics

1. Excellent high temperature oxidation stability – prevent the machine from sludge formation during high temperature of operation.
2. Prevent sludge formation by the residual oil contamination and deterioration of cutting oil mist.
3. Excellent rust prevention ability & water separation performance – prevent the moisture in the air to mix in the oil causes corrosion to compressor, water content is easily drained out.
4. Strong copper corrosion inhibitor – prevent oil from deteriorating and changing in quality by the influence of copper.

Available ISO grade

VG32, VG46 & VG68

Packing

20L Pail & 200L Drum

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement. Please refer to Material Safety Data Sheet for any safety issue concern which can be obtained from your nearest Idemitsu reseller.

Lubricant Product Information**Typical Specifications****Daphne Super Screw Series**

	TYPE OF TEST METHOD	<u>VG 32</u>	<u>VG 46</u>	<u>VG 68</u>
Density 15 °C g/cm ³	ASTM D-4052	0.8654	0.8685	0.8735
Colour	ASTM D-1500	L0.5	L0.5	L1.5
Flash Point (COC) °C	D-92	228	230	255
Viscosity, cSt @ 40 °C, mm ² /s	D-445	32.53	45.34	69.53
		@ 100 °C mm ² /s	5.458	6.793
TAN (mgKOH/g)	D-974	0.05	0.07	0.08
Copper Corrosion (100°C x 3h)	D-130	1(1B)	1(1B)	1(1B)
RBOT Value	-	1920	1860	-

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement. Please refer to Material Safety Data Sheet for any safety issue concern which can be obtained from your nearest Idemitsu reseller.