Charger Electric Model HLE



Rugged.... Durable.... Harlan



Standard Features

High Efficiency AC Motor allows for longer duty
cycles between charges
AC Pump Motor
Keyless or Keyed master Switch
Two LED Headlights and turn signals
Combination LED Tail/Stop Lights & Back-up Light
Safety kill switch on driver's seat
LCD Dash Display
Fwd & Rvs Inching
Standard Driver and Passenger seat
Retractable Seatbelts
Rear Mount E-Hitch


Available with Lithium-ion or Lead-acid, the Harlan Model "Charger HLE" is equipped to handle all your light duty baggage and cargo needs. The low maintenance electric package is designed for easy access to all major components.

By adding the push-back package this unit can also be utilized for push-back of regional jets up to 100K (45359kg). Some options include: complete cab assembly, heat/defrost, mirrors, beacons, variety of hitches and suspension style seats.





Specifications



Length

116.28" (2953 mm)

w/rear hitch: 122" (3099 mm)

Width

52" (1321 mm)

w/ Cab: 54.25 (1376 mm)

Height

52" (1321 mm)

w/ Cab 75.28" (1930 mm)

Wheel Base

64.25" (1632 mm)

Ground Clearance

7.25" (184.5 mm)

Integrated Drive Axle

Fully integrated with AC

Induction Motor

Service Brakes

Primary: 4-Wheel Hydraulic

Secondary: Traction motor

braking with regen

Towing Coupler

E-Hitch w/1" pin

(other options available)

Tires

Front: 6.50 x 10

Back: 7.00-15

Controller

Curtis Programable

Energy Source

8NV Lithium-inn or 8NV Lead-acid

Charging Options

- -On Board Charger
- -EV Interface (used w/ on board charger
- -Standard Charger
- -Fast Charge connection set-up

Steer Axle

Heavy-Duty Harlan with 1

1/8" Kingpin

Suspension

Front: Leaf spring w/ Shocks

Rear: Coil spring w/ Shocks

Steering System

Hydrostatic


Park Brake

Electric actuated









DRAW BAR PULL

HLE45	HLE50	HLE60	HLEPB
4,500 lbs. (20kN)	5,000 lbs. (22kN)	6,000 lbs. (26.7kN)	Regional Jet up to 100K

