TransCon-e Electric Model HTSBEL



Rugged.... Durable.... Harlan



Standard Features

High Efficiency AC Motor allows for longer duty
cycles between charges
AC Pump Motor
Keyless or Keyed master Switch
Two LED Headlights and turn signals
Combination LED Tail/Stop Light & Back-up
Light Safety kill switch on driver's seat
Electric Actuated Park Brake
LCD Dash Display
Fwd & Rvs Inching
Standard Driver and Passenger seat
Retractable Seatbelts
Rear Mount F-Hitch


The Harlan Model HTSBEL Lithium-ion powered baggage/cargo tractor was developed to meet the demands of the growing market for Lithium powered electric vehicles. With many of these units in service since 2014 Harlan has the experience needed for this new technology.

This popular electric package in the familiar baggage/cargo tractor frame aircraft is crafted to meet the challenging demands of ramp life. Some options include complete cab assembly, heat/defrost, mirrors, beacons, variety of hitches and suspension style seats.





Specifications



Length

105.75" (2687mm)

w/ rear hitch: 113" (2891 mm)

Width

57.5" (1460 mm)

Height

56.5" (1435 mm)

w/ Cab 81.5" (2070 mm)

Wheel Base

60 3/8" (1534 mm)

Ground Clearance

7.75" (196.8mm)

Integrated Drive Axle

Fully integrated with AC

Induction Motor

Steer Axle

Heavy-Duty Dual Shaft with two tapered roller bearings

Towing Coupler

E-Hitch with 1" pin (other hitch

options available)

Tires

Front: 165/R13

Back: LT225/75Rx16

Controller

Curtis Programable

Energy Source

80V Lithium-ion

Charging Options

- -On Board Charger
- -EV Interface (used w/on board)
- -Fast Charge connection set-up

Steering System

Hydrostatic

Service Brakes

Primary: 4-Wheel Hydraulic

Secondary: Traction motor


braking with regen Suspension

Front: Leaf spring

Rear: Coil spring w/ Shocks

Park Brake

Electrically actuated









DRAW BAR PULL

| HTSBEL40 | HTSBEL50 | HTSBEL60 |
|--------------------|---------------------|---------------------|
| 4,000 lbs. (17.8N) | 5,000 lbs. (22.2kN) | 6,000 lbs. (26.7kN) |

